

## National Risk Assessment Partnership (NRAP)

Grant S. Bromhal

NRAP Technical Coordinator

Geosciences Division
















## National Risk Assessment Program (NRAP)

Develop a defensible, science-based methodology and platform for quantifying risk profiles at most types of CO<sub>2</sub> storage sites in order to guide decision making and risk management by reducing uncertainty in the business case for long-term storage.



## **National Risk Assessment Partnership:**

Leveraging DOE's Science-Based Prediction Capability to Build Confidence in Engineered–Natural Systems

How effective is geologic storage of CO<sub>2</sub> (e.g., will it leak)?

- What is the value of potential long-term liabilities?
- What is the most effective and efficient approach to environmental monitoring post injection?
- What are the best protocols to mitigate potential for induced seismicity?

#### **Two Key Goals**

- develop toolset and supporting data for sciencebased risk assessments
  - already completed the first generation toolset to predict leakage impacts and potential for induced seismicity
- build confidence in key storage-security relationships to support decisions
  - initiating phase to apply first generation toolset to elucidate storagesecurity relationships
































### NRAP Approach to Quantifying System Performance















## **Reservoirs**














**Key NRAP Accomplishments/Results: Reservoirs** 


#### **Tool & Method Development**

- Produced ROMs for three reservoirs
  - Kimberlina-like; 5 Mt/yr CO<sub>2</sub> (fixed) over 50 yrs injection only; 150 yrs relaxation; sandstone w/ interbedded shale & shale caprock
  - Otway-based; up to 0.5 Mt injection (variable rate) for 10 yrs; 500 yrs of relaxation; sandstone gas reservoir
  - SACROC-based; history-matched multiple well injection over 50 yrs;
     1000 yrs of relaxation; carbonate reef EOR site
- Preliminary evaluations for 4 ROM approaches
  - Simple look up table
  - Surrogate reservoir model based on artificial intelligence
  - Polynomial chaos expansion
  - Gaussian regression analysis


#### **General Trends & Relationships**

- Pressure and saturation at reservoir-seal interface is sensitive to only a few key subsurface parameters
  - Caprock permeability is key in predicting pressure relaxation





Permeability I (md) 2172-01-01















#### **SACROC Oil Field Model**

#### Saline Sandstone Reservoir Within Depleted Gas Field

- Based on actual EOR field in West Texas (40 years of CO<sub>2</sub> injection)
- Upscaled porosity and permeability model from University of Utah
- 10 CMG simulations with history-matched model, begin after oil production completed
- Allow injection for 50 years in several wells at a given wellhead pressure
- Surrogate model based on artificial intelligence and data mining approach using neural networks

**Porosity** 

Permeability













# Polynomial Chaos Expansion for SACROC ROM Development – Work in Progress

```
Inputs:
Time (t)
k1, k2, k3, k4,...
% of lithostatic pressure (pct)

polynomial(k1,k2,k3,k4,...pct,t)
```


Outputs of layer 18 gridblock:

- Pressure
- Saturation(water, oil, CO2)

Total PCEs = 544 gridblocks  $\times 4$  outputs = 2176 PCEs



- 1. Design reservoir simulation inputs
- 2. Reservoir simulation
- 3. Train PCE model















# Migration Pathways (Wellbores and Seals)
















### NRAP Migration Pathways Working Group


#### Well Scale Reduced Order Models for Risk Profiles


#### **Laboratory Experiments to Address Science Gaps**















#### Single Fracture Models to Simulate Opening/Closing of Flow Paths







#### **Field Data Analysis for Validation**



Aperture distributions (LHS) and pore-fluid velocities (RHS) from GEOS simulations of a natural fracture under atmospheric and 20 MPa confining pressure.















## CO<sub>2</sub> and Wellbore Leakage Risk

- Experimental and numerical studies of flow through damaged cements.
- Objective is to predict timedependant leak rates.

 Provide evidence for self limiting or self enhancing leakage.


































## **Groundwater**















### **Key NRAP Accomplishments/Results: Groundwater**

#### **Tool & Method Development**

- Established "no-impact" threshold values for two different classes of aquifers
  - High Plains confined sandstone aquifer
  - Edwards unconfined limestone aquifer
- Developed ROMs to predict impacts of CO<sub>2</sub> and brine leakage on pH, TDS and trace metals in each class of aquifer for MCL or "no-impact" thresholds
  - LLNL: sandstone, confined, 3D, multiple leaky wells, flow, transport, hydraulic heterogeneity, simple geochemistry
  - LBNL: sandstone, confined, 1D, complex geochemistry
  - LANL: limestone, unconfined, 3D, multiple leaky wells, flow, transport, hydraulic heterogeneity, simple geochemistry
  - PNNL: limestone, unconfined, 2D, complex geochemistry
- Developing linking functions to combine complex hydraulics and geochemistry ROMs for each class of aquifer
- Conducting experiments to determine impact of CO<sub>2</sub> leakage on major elements and trace metals using aquifer sediments from each class of aquifer

















## Key NRAP Accomplishments/Results: Groundwater

#### **General Trends & Relationships**


#### Confined Sandstone Aquifer:


- Adsorption/desorption is the most important process that controls trace-metal impacts due to the intrusion of CO<sub>2</sub>
- 0.01–0.1% of the CO<sub>2</sub> in the aquifer leaks to atmosphere
- Developed relationships to assess impact of metal-transport by brine on aquifer chemistry (for Cd, As, Pb, Cr)
- Chemical-Hydraulic linking function is a promising way to lower the computation load for derivation of ROM and improve prediction of volume affected by CO<sub>2</sub> intrusion

#### Unconfined Limestone Aquifer:

- Volume of pH impact is sensitive to CO<sub>2</sub> leak rate, total CO<sub>2</sub> mass, porosity and permeability
- Leak rates are most significant parameters for pH, TDS and trace metal concentrations, but carbonate equilibria and clay sorption are also important
- 69% of simulations have CO<sub>2</sub> atmospheric leak rates >0 and 52% of simulations have atmospheric leak rate >80% of wellbore leak rate
- Plume sizes for trace metals are notably larger using no-impact thresholds
- The quadratic and cubic ROMs for the 8 output variables are the best models and can be used for system-level predictions of hydraulic impacts

#### Limestone Aquifer

















## **Monitoring**
















## Fault and Fracture Zone Detection and Reduced Order Fracture Model Development for Risk Assessment




Teapot Dome



Post-stack enhancements adaptive to non-stationary signal



San Juan Basin Pilot



Our efforts have been used to enhance possible fracture zones and fault networks and to identify potential leakage zones in three areas including the San Juan Basin (New Mexico), Teapot Dome (Wyoming) and the Central Appalachian foreland (West Virginia).

















## Waveform Attribute Analysis to Detect Potentially Leaky Faults









Test case in a fractured reservoir. Note the enhanced imagery of reservoir and cap rock fractures













## **Systems Modeling**














## Reservoir Dashboard















## Wellbore

Updated the well data input dashboard

Well Data (Location & Types)  Multiple known wells with location input through input file				
Multi-segmented wells				
Randomly Placed Wells			Known Wells	
Number of Wells Number of Wells  Based on Distribution Based on We			Number of Known	1
Mean Standard Deviation	Wells/km2		Plugged Wells	
Define area for placing random wells			X, Y location of single known well	
Xmin (m)	Ymin (m)	Xmin (m)	Ymin (m)	
Xmax (m)	Ymax (m)			
Distribution of well types for random wells (well type percentage sum should equal to 100%)				
1 2 3 4 5 6 7 8 9 10   Percentage [%] 0 0 0 0 100 0 0 0 0 0 0 0 0 0 0 0 0 0				
	Cement Permeability	<u>'</u>	Back to Storage	Back to MAIN














## Fault ROM dll in CO<sub>2</sub>-PENS


















## **Key NRAP Accomplishments/Results: System Models**


#### **Tool & Method Development**

- Developed first-ever integrated assessment model for predicting for leakage impacts
  - Approach integrated ROMs for storage reservoir, wellbores (open & cemented), faults and shallow aquifer
  - IAM used to generate risk profiles and associated uncertainties for three metrics (release to atmosphere, change in pH in shallow aquifer, change in TDS in shallow aquifer)
- Developed second generation IAM for leakage impacts
  - Updated first generation IAM with second generation ROMs
  - Second generation ROMs have increased process complexities and wider parameter range

#### **General Trends & Relationships**

- Leakage Impacts
  - The calculated risk profiles show significantly different qualitative behavior compared to "Benson" profile
  - "Preliminary" risk profiles show extremely low risks for the three leakage metrics considered for first generation
  - Uncertainties in wellbore cement permeability dominate overall uncertainties

















## **Induced Seismicity**














## Key NRAP Accomplishments/Results: Induced Seismicity

#### **Tool & Method Development**


- Developed first-ever probabilistic seismic hazard assessment (PSHA) tool for induced seismicity
  - adapted widely accepted conventional PSHA approach
- Extending development to assess damage and nuisance (felt event) risks
  - demonstration application to realistic CO<sub>2</sub> injection scenarios

#### **General Trends & Relationships**

- Rates of occurrence and sizes of earthquakes are determined by tectonic stress and reservoir pressure
  - sensitive to fault permeability and a few key parameters in the law governing the evolution of fault frictional strength
- Risk of CO<sub>2</sub> leakage may be affected by slip on faults during earthquakes, requires integration with systems leakage model



Pore pressure
















## Energy Data eXchange is being used as tech transfer mechanism for technical reports, tools, and datasets.















### **NRAP Team Members**

Rajesh Pawar, Grant Bromhal, Robert Dilmore, Jason Gastelum, Edwin Jones, Jason Monnell, Curt Oldenburg, Philip Stauffer, Yingqi Zhang, Liange Zheng, Marco Bianchi, Jens Birkholzer, Nicolas Spycher, Susan Hubbard, Preston Jordan, Peter Nico, John Peterson, Charu Varadharajan, Yuxin Wu, Susan Carroll, Yue Hao, Kayyum Mansoor, Yunwei Sun, and Sharon Torres, Elizabeth Keating, Zhenxue Dai, Dennis Newell, and Hari Viswanathan, Alexandra Hakala, Christina Lopano, Athanasios Karamalidis, Maneesh Sharma; Rosemary Capo, Brian Stewart, James Gardiner; Craig Griffith, Diana Bacon, Chris Brown, Kirk Cantrell, Omar Harvey, George Last, Chris Murray, Nik Qafoku, and Hongbo Shao, Angela Goodman, Shahab Mohaghegh, Shohreh Amini, Vidi Gholami, Alireza Shahkarami, Nick Sahinidis, Yan Zhang, Wei Jia, Brian McPherson, Jens Birkholzer, Haruko Wainwright, Yingqi Zhang, George Pau, Chris Doughty, Quanlin Zhou, Stefan Finsterle, Susan Carroll, Yue Hao, Chuanhe Lu, Diana Bacon, Mark White, Yilin Fang, Kirk Cantrell, Rajesh Pawar, Phil Stauffer, Hailin Deng, Brian Strasizar, Bill Carey, Bill Harbert, Dengling Gao, Tom Wilson, Erik Westman, Hema Siriwardane, Josh White, Bill Foxall ++













## **Questions?**

· Thanks!

bromhal@netl.doe.gov











